

Recap: *What* an object can do

- Defined by its *interface*
 - Consists of *public methods* and *public data*
- Accomplished by its *implementation*
 - Includes *private members* and *internal details* of methods
- A `class` provides both the interface and implementation for objects of a particular type
 - Defines the public interface
 - Defines the data that objects store
 - Implements the methods (both public and private)

Label objects for example

- Public interface – what clients need to know
 - Includes **accessors**: `public String getText()`
 - And **mutators**: `public void setText(String text)`
 - Even constants: `public static final int CENTER`
 - Also `LEFT` and `RIGHT` – where to display the text
- Implementation is in **class** `(java.awt.)Label`
 - Defines the public methods – so they actually work
 - Has non-public features too: `text`, `alignment`, ...
 - Includes methods that clients don't have to know about
 - Reason: these parts can change without ruining client's work

A custom example: BankAccount

- A software designer identified the need for objects that represent bank accounts
 - Part of a banking system, or personal portfolio, or ...
- Q: *Why objects, not just numbers?*
 - A: bank accounts are more complex than numbers
 - Include **data** (balance, account holder information, ...)
 - And **methods** (controlled ways to deposit and withdraw, ...)
- Idea is that other software objects will:
 - Create **new BankAccount** objects
 - Use the objects' public features to solve problems

Notes about choosing classes

- A class represents a concept from the problem domain
- Name for a class – a noun that describes the concept
 - e.g., geometric concepts: Point, Rectangle, Ellipse, ...
 - Or real life concepts: BankAccount, CashRegister, ...
- Lots of general types of concepts/classes:
 - e.g., Actors (end in -er, -or) – do some kinds of work for you
 - Scanner is a good example
 - Random is not (better name would be RandomNumberGenerator)
 - e.g., Utilities (like Math) – often just static methods/constants
 - e.g., Program starters – only have a main method
- Advice: don't turn actions into classes
 - e.g., Paycheck is better name than ComputePaycheck

Accessor and mutator methods

- Accessors – to allow access to private data
 - Usually call same as variable, or getVariable
 - e.g.,

```
private int var; ...  
public int getVar() { return var; }
```
 - Note: only if other classes *need* such access
- Mutators – to allow changes to private data
 - e.g., deposit and withdraw methods of BankAccount
 - Basic mutators are usually called “set” methods
 - ```
public void setVar(int x) { var = x; }
```
  - Note: only if other classes *should* change the data, and only in ways that keep the object in a valid state

# Notes about `this`

- `this` is an object reference – a constant an object uses to refer to itself (“me” better reflects the concept)
- e.g., print me: `System.out.print(this);`
- Often just an *implicit* reference: `calculate();`
  - Same as explicitly saying `this.calculate();`
  - Also the case for instant variables: `x ↔ this.x`
    - See [ThisTest.java](#) (Fig. 8.4, pp. 323-324)
- Has a special purpose for overloaded constructors
  - See [Time2.java](#) (Fig. 8.5, pp. 325-327)
- Has no meaning (so illegal to use) in a static context

# Predicate methods

- Methods that return a boolean value
  - e.g., BankAccount enhancement:

```
public boolean isOverdrawn() {
 return balance < 0;
}
```
- Can simplify and clarify programs that use them

```
if (myAccount.isOverdrawn()) ..
```
- Lots of API examples
  - e.g., Scanner: `input.hasNextInt()`
  - e.g., Stack: `stack.isEmpty()`
  - e.g., Character: `Character.isDigit(aChar)`

# Avoid “side effects” of methods

- Any *externally* observable data modification
- e.g., modifying an explicit parameter

```
void transfer(double amount, Account other){
 balance = balance - amount;
 other.balance = other.balance + amount;
}
```

- Unexpected output is another example
  - i.e., don't print unless that is the method's purpose
  - In fact, any printing at all might cause problems

```
public void printBalance() { // Not recommended
 System.out.println("Balance is $" + balance);
}
```

- Now only works in English locale
- Also relies on System.out – might not be available in GUI



# Packages

- Uppermost level of Java modules
  - Used to bundle related classes – a good design idea
- Declare in each class – `package my.stuff;`
- Store all in same directory – `./my/stuff/`
- Must qualify class names to use them
  - Either explicitly each time name is used – `my.stuff.Thing`
  - Else `import my.stuff.Thing;`
  - Or `import my.stuff.*; //` to get all classes in package
- See text section 8.16 (and related Fig. 8.19 and Fig. 8.20)
- Package access – a.k.a. “friendly” – no access modifier

# Applets – an alternate approach

- A way to run a program – but *not an application*
  - No `main` method necessary
- Need a **subclass** of `Applet` (or `JApplet`)
  - So: `class __ extends Applet` (or `extends JApplet`)
- Most web browsers know how to create a new applet, and how to use certain `Applet` methods
  - So, applets must be embedded in an **html** page
  - And, to be useful, they must include at least one of the methods the browser invokes (e.g., `paint`)

# “Running” an Applet

- The applet is started by the web browser as soon as the web page (html file) is visited
- The html file (stands for hypertext markup language) — must have an applet tag in it:

```
<html> ...
<applet code=AppletClassName.class
 width=### height=###>
</applet> <!-- needs a closing tag too -->
... </html>
```

# FYI: a little more html

- All based on **tags** – which come in pairs
  - e.g., italics – “a `<i>stressed</i>` word” – would show on web page as “a *stressed* word”
  - Also underline - `<u>...</u>`, bold - `<b>...</b>`, subscript - `<sub>...</sub>`, and so on
  - Can nest like “`<b><u>ok</u>ay</b>` then!” shows up as “okay then!”
    - But wrong if not *nested*, like “`<b><u>...</b></u>`”
- Best kind of tags are **hyperlinks**
  - e.g., “`<a href=http://www.ucsb.edu>my school</a>`” shows up like “my school”
- See any of many web resources

# Implementing a “simple” applet

- `import javax.swing.JApplet; // mandatory`
  - Also usually `Graphics` and `Graphics2D` and others
- Declare a class that extends `JApplet`:  
`public class RectangleApplet extends JApplet`
- Implement `paint` method (at least)
  - Same procedures as `paintComponent` for components
- Create an html file to load the applet in a web browser or the `appletviewer` (provided with JDK)
- e.g., [RectangleApplet.java](#) (see link on Slides page)

# Notes on *rendering* text

- Actually necessary to “draw” the text at a specified location on the Graphics object
  - `g.drawString(aString, x, y)`
  - Uses current rendering context (e.g., color), and current text attributes (e.g., font)
- Font: a *face* name, a *style*, and a point *size*

```
Font f = new Font("Serif", Font.BOLD, 24);
g.setFont(f); // now drawString uses this font
```
- Note: often can just use a JLabel to show in adjacent component
  - Other text display components too – even Text objects

# Various applet examples

- [FontApplet](#) – fonts, and text centering
- [TicTacToe](#) – converting units to pixels
  - Note: vertical axis increases downward – so must flip y coordinates if drawing typical graph
- [ImageApplet](#) – displaying/scaling images
- [EggApplet](#) – handling mouse events
- [ColorSlider](#) – slider (state-change) events

Note: all of these programs could have been applications instead. Don't need applets to have graphical features in programs – just to include the programs on a web page.

# 5JA done! Where to go from here?

- Much deeper computer science to study
  - 1<sup>st</sup> take CS 10 – if you still like it, take more
- Many other programming languages out there
  - Beginning C is part of Engineering 3 curriculum
  - C++, VisualBasic, C#, ... at UC Extension, SBCC, and tech schools like SB Business College
  - But you *can* learn them by yourself now too!
    - For specifics: just get a book, and/or look for online tutorial
- Lots more Java techniques to learn about
  - Suggest starting with Java Tutorial – books, and online at <http://java.sun.com/docs/books/tutorial/>